

Hoses: Pyrojacket®

INSULFLEX®



Technical Specification

- Sizes: 1/4" to 5"
- Material: High bulk glass knitted fibre
- Continuous operating temperature: 500°F (260°C)
- Max short term exposure: 3000°F (1650°C)
- Molten splash resistance: Outstanding
- Flame resistance: Very good
- Abrasion resistance: Very good
- Flexibility: Outstanding
- Water and oil resistance: Outstanding

Features & Benefits

- Sheds splash immediately
- Withstands intense radiant heat and flame
- Protects personnel & cuts energy losses
- Guards against fraying and absorption

Applications

- High temperature conveying
- Molten steel
- Molten aluminium
- Molten glass

Code	Inside Diameter
Industrial grade Pyrojacket® Fire Sleeve	
PYRO PJ-04	1/4"
PYRO PJ-05	5/16"
PYRO PJ-06	3/8"
PYRO PJ-07	7/16"
PYRO PJ-08	1/2"
PYRO PJ-10	5/8"
PYRO PJ-12	3/4"
PYRO PJ-14	7/8"
PYRO PJ-16	1"
PYRO PJ-18	1 1/8"
PYRO PJ-20	1 1/4"
PYRO PJ-22	1 3/8"

Product Group & Name Title

Code	Inside Diameter
PYRO PJ-24	1 1/2"
PYRO PJ-26	1 5/8"
PYRO PJ-28	1 3/4"
PYRO PJ-32	2"
PYRO PJ-36	2 1/4"
PYRO PJ-40	2 1/2"
PYRO PJ-44	2 3/4"
PYRO PJ-48	3"
PYRO PJ-52	3 1/4"
PYRO PJ-56	3 1/2"
PYRO PJ-60	3 3/4"
PYRO PJ-64	4"
PYRO PJ-72	4 1/2"
PYRO PJ-80	5"

