

Model		6 motor												
Voltage	V	100	100	120	200	200	230	230						
Frequency	Hz	50	60	60	50	60	50	60						
Motor	HP	0,54	0,54	0,54	0,46	0,46	0,46	0,46						
	kW	0,40	0,40	0,40	0,34	0,34	0,34	0,34						
Displacement	l/min	50	60	60	50	60	50	60						
	CFM	1,77	2,12	2,12	1,77	2,12	1,77	2,12						
FAD @ 8 bar	l/min	32	37	37	32	37	32	37						
	CFM	1,13	1,31	1,31	1,13	1,31	1,13	1,31						
Max. Pressure ¹⁾	bar	8	8	8	8	8	8	8						
	psi	120	120	120	120	120	120	120						
Max. Current	A	5,7	5,2	6,2	2,9	2,9	2,9	2,9						
Weight	kg	14	14	14	14	14	14	14						
	lbs	31	31	31	31	31	31	31						
Dimensions	mm	280 x 190 x 240												
(l x w x h)	inch	11 x 7 4/8 x 9 4/8												
Noise level	dB(A)/1m	45	45	45	45	45	45	45						

¹⁾ Higher pressure available upon request
 Technical modifications reserved

Model		6 - 4												
Voltage	V	100	100	120	200	200	230	230						
Frequency	Hz	50	60	60	50	60	50	60						
Motor	HP	0,54	0,54	0,54	0,46	0,46	0,46	0,46						
	kW	0,40	0,40	0,40	0,34	0,34	0,34	0,34						
Displacement	l/min	50	60	60	50	60	50	60						
	CFM	1,77	2,12	2,12	1,77	2,12	1,77	2,12						
FAD @ 8 bar	l/min	32	37	37	32	37	32	37						
	CFM	1,13	1,31	1,31	1,13	1,31	1,13	1,31						
Max. Pressure ¹⁾	bar	8	8	8	8	8	8	8						
	psi	120	120	120	120	120	120	120						
Max. Current	A	5,7	5,2	6,2	2,9	2,9	2,9	2,9						
Tank size	liter	4	4	4	4	4	4	4						
	gallon	1,1	1,1	1,1	1,1	1,1	1,1	1,1						
Weight	kg	23	23	23	23	23	23	23						
	lbs	51	51	51	51	51	51	51						
Dimensions	mm	384 x 333 x 342												
(l x w x h)	inch	15 1/8 x 13 1/8 x 13 4/8												
Noise level	dB(A)/1m	45	45	45	45	45	45	45						
Pumping time (0-8 bar /0-120 psi)	sec.	60	50	50	60	50	60	50						

¹⁾ Higher pressure available upon request
 Technical modifications reserved