


VALVOLE 2 VIE FILETTATE CON ATTUATORE
2 WAY THREADED VALVES WITH ACTUATOR



 Valvola a sfera 2 vie in ottone, passaggio totale secondo norma DIN 13547 [RB art. 2500] filettatura F/F non idonea per solventi.

 2 way, brass ball valve, full bore according to DIN 13547 [RB art. 2500] threaded F/F, not suitable for use with solvents.



Art. 8P007900 Con attuatore pneumatico doppio effetto serie 82.
 With double acting pneumatic actuator series 82.

MISURA-SIZE	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
PN	40	40	40	40	40	40	40	40	25	16	16
ACT.	DA32	DA32	DA32	DA32	DA32	DA32	DA52	DA52	DA63	DA63	DA85
KIT	RI4015	RI4015	RI4015	RI4015	RI4015	RI4015	RI4016	RI4016	RI4021	RI4021	RI4021



Art. 8P008100 Con attuatore pneumatico semplice effetto serie 82.
 With spring return pneumatic actuator series 82.

MISURA-SIZE	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
PN	40	40	40	40	40	40	40	40	25	16	16
ACT.	SR52	SR52	SR52	SR52	SR52	SR52	SR63	SR63	SR85	SR85	SR100
KIT	RI4017	RI4017	RI4017	RI4017	RI4017	RI4017	RI4018	RI4018	RI4020	RI4020	RI4029

Art. 8P014*** Con attuatore elettrico serie 85.
 With electric actuator series 85.

MISURA-SIZE	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
PN	40	40	40	40	40	40	40	40	25	16	16
ACT.	VB015	VB015	VB015	VB015	VB015	VB015	VB030	VB030	VB060	VB060	VB110
KIT	RI4017	RI4017	RI4017	RI4017	RI4017	RI4017	RI4016	RI4016	RI4021	RI4021	RI4021
12 V											
24 V											
100 - 240 V											

*** CODICE TENSIONE - VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004